


ROGGA

147-0708101240496660


ROGGA S SWITCH W SURFACE MOUNTED WALL LUMINAIRE made of aluminium, black, similar to RAL 9005, decor black,high-efficiently vacuum deposited aluminium reflector beam 50°, light output direct, swiveling 350°, tilting 110°, with converter, max. 300mA, dimmability: not dimmable, adapter/ceiling base black, IP20



SKETCH



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

Light source	LED
System performance [W]	11,5
Luminous flux [lm]	1150
Current sec. [mA]	300
Colour temperature	3000K
CRI	PREMIUM>90
Optics	vacuum deposited aluminium reflector
Converter	with converter
Dimmability	not dimmable
Light emission area	direct
Beam angle	50°
Voltage	220-240V 50/60Hz
Length [mm]	110
Width [mm]	50
Height [mm]	33
Diameter [mm]	41
IP protection class	IP20
IP protection class	protection cl. I
Material	aluminium
Colour of body	black
RAL	9005
Colour of adapter / ceiling base	black
Colour of decor	black
Lifetime [h]	L80 B10 50 000
Energy efficiency class	E
Number of luminaires B16A	50
Net weight [kg]	0.65
EAN number	9010979335769



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.