

# LOG 2.1

728-601054013050

LOG 2.1 SYSTEM EINSATZ D/ID LIGHT INSERT made of metal, white, similar to RAL 9016, light output direct / indirect, with converter, max. 900mA, dimmability: not dimmable, through wiring 3x1,5mm², IP20



## TECHNICAL DETAILS

|                           |                   |
|---------------------------|-------------------|
| Light source              | LED               |
| System performance [W]    | 79                |
| Luminous flux [lm]        | 12530             |
| Current sec. [mA]         | 900               |
| Colour temperature        | 2700K             |
| CRI                       | >80               |
| Converter                 | with converter    |
| Dimmability               | not dimmable      |
| Light emission area       | direct / indirect |
| Voltage                   | 220-240V 50/60Hz  |
| Through wiring            | 3x1,5mm²          |
| Length [mm]               | 1403              |
| IP protection class       | IP20              |
| IP protection class       | protection cl. I  |
| Material                  | metal             |
| Colour of body            | white             |
| RAL                       | 9016              |
| Lifetime [h]              | L80 B10 50 000    |
| Energy efficiency class   | D                 |
| Number of luminaires B16A | 25                |
| Net weight [kg]           | 2.00              |
| EAN number                | 9010506153682     |



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.  
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.