


TRAIL

610-130005134966d

TRAIL MOVA M MOUNTING RAIL LIGHT INSERT made of aluminium, black, similar to RAL 9005, decor black,high-efficiently vacuum deposited aluminium reflector without safety glass beam 40°, light output direct, swiveling 350, tilting 90, with converter, max. 1050mA, dimmability: DALI 2 DATA, through wiring 7-polig, adapter/ceiling base black, IP20




SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	40
Luminous flux [lm]	4660
Current sec. [mA]	1050
Colour temperature	3000K
CRI	PREMIUM>90
Optics	aluminium reflector without protection glass
Converter	with converter
Dimmability	DALI 2 DATA
Light emission area	direct
Beam angle	40°
Voltage	220-240V 50/60Hz
Through wiring	7-polig
Length [mm]	564,9
Height [mm]	156
Diameter [mm]	82
IP protection class	IP20
IP protection class	protection cl. I
Material	aluminium
Colour of body	black
RAL	9005
Colour of adapter / ceiling base	black
Colour of decor	black
Lifetime [h]	L80 B10 50 000
Energy efficiency class	E
Number of luminaires B16A	50
Net weight [kg]	0.96
EAN number	9010870133532

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.