



DIVO

192-202020002355d

DIVO SHORT PD SUSPENSION made of aluminium, white, similar to RAL 9003, high quality plastic lens beam 36°, light output direct, with converter, max. 250mA, dimmability: DALI, cable white, adapter/ceiling base white, pendant length 3000mm, IP20




SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	11
Luminous flux [lm]	680
Current sec. [mA]	250
Colour temperature	2700K
CRI	>90
Optics	high quality plastic lens with converter
Converter	DALI
Dimmability	direct
Light emission area	36°
Beam angle	220-240V 50/60Hz
Voltage	
Length [mm]	300
Length pendant [mm]	3000
Diameter [mm]	57
IP protection class	IP20
IP protection class	protection cl. II
Material	aluminium
Colour of body	white
RAL	9003
Colour of adapter / ceiling base	white
Cable	white
Lifetime [h]	L80 B10 20 000
Energy efficiency class	F
Net weight [kg]	1.30
EAN number	9010506764024

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.