



DIVO

192-202020002966d

DIVO SHORT PD SUSPENSION made of aluminium, black, similar to RAL 9005, high quality plastic lens beam 36°, light output direct, with converter, max. 250mA, dimmability: DALI, cable black, adapter/ceiling base black, pendant length 3000mm, IP20




SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	11
Luminous flux [lm]	680
Current sec. [mA]	250
Colour temperature	3000K
CRI	>90
Optics	high quality plastic lens with converter
Converter	DALI
Dimmability	direct
Light emission area	36°
Beam angle	220-240V 50/60Hz
Voltage	
Length [mm]	300
Length pendant [mm]	3000
Diameter [mm]	57
IP protection class	IP20
IP protection class	protection cl. II
Material	aluminium
Colour of body	black
RAL	9005
Colour of adapter / ceiling base	black
Cable	black
Lifetime [h]	L80 B10 20 000
Energy efficiency class	F
Net weight [kg]	1.38
EAN number	9010506764093

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.