

TUNE

157-011001011444a


TUNE S PC HIGH-BAY REFLECTOR LUMINAIRE made of aluminium, grey, similar to RAL 9006, high quality plastic lens beam 75°, accessoire: PC, light output direct, with converter, max. 3400mA, dimmability: switchable, 1-10V, IP66



SKETCH



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

Light source	LED
System performance [W]	150
Luminous flux [lm]	20380
Current sec. [mA]	3400
Colour temperature	4000K
CRI	>80
Optics	high quality plastic lens
Converter	with converter
Dimmability	switchable, 1-10V
Light emission area	direct
Beam angle	75°
Voltage	220-240V 50/60Hz
Length [mm]	280
Height [mm]	176
Diameter [mm]	280
IP protection class	IP66
IP protection class	protection cl. I
IK value	IK10
Material	aluminium
Colour of body	grey
RAL	9006
Lifetime [h]	L80 B10 70 000
Ambient temperature	from -30° to +45°
Energy efficiency class	D
Number of luminaires B16A	7
IFS	True
Net weight [kg]	1.81
EAN number	9010506734850



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.