

TUNE

157-0211110114442

TUNE M PC BWS HIGH-BAY REFLECTOR LUMINAIRE made of aluminium, silver, similar to RAL 9006, high quality plastic lens beam 75°, accessoire: ball grid, light output direct, UGR <22, with converter, max. 3000mA, dimmability: DALI 2 DATA, IP66



SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	150
Luminous flux [lm]	21900
Current sec. [mA]	3000
Colour temperature	4000K
CRI	>80
UGR	<22
Optics	high quality plastic lens
Converter	with converter
Dimmability	DALI 2 DATA
Light emission area	direct
Beam angle	75°
Voltage	220-240V 50/60Hz

Length [mm]	362,1
Height [mm]	186
Diameter [mm]	360
IP protection class	IP66
IP protection class	protection cl. I
IK value	IK10


Material	aluminium
Colour of body	grey
RAL	9006
Lifetime [h]	L80 B10 70 000
Ambient temperature	from -30° to +50°
Energy efficiency class	D
Number of luminaires B16A	7
IFS	True

Net weight [kg]	2.31
EAN number	9010506737349



Energy label

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.