

DIVO

192-2090200023540

DIVO SHORT VOLARE SUSPENSION WITH 2-PH VOLARE ADAPTER made of aluminium, white, similar to RAL 9003, high quality plastic lens beam 36°, light output direct, with converter, max. 260mA, dimmability: not dimmable, cable white, adapter/ceiling base silver, pendant length 3000mm, IP20



SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	12
Luminous flux [lm]	680
Current sec. [mA]	260
Colour temperature	2700K
CRI	>90
Optics	high quality plastic lens
Converter	with converter
Dimmability	not dimmable
Light emission area	direct
Beam angle	36°
Voltage	220-240V 50/60Hz
Length [mm]	3000
Height [mm]	300
Length pendant [mm]	3000
Diameter [mm]	57
IP protection class	IP20
IP protection class	protection cl. II
Material	aluminium
Colour of body	white
RAL	9003
Colour of adapter / ceiling base	silver
Cable	white
Lifetime [h]	L80 B10 20 000
Energy efficiency class	G
Net weight [kg]	1.16
EAN number	9010506772647

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.