## DIVO


## 192-2090200023640

DIVO SHORT VOLARE SUSPENSION WITH 2-PH VOLARE ADAPTER made of aluminium, black, similar to RAL 9005,high quality plastic lens beam 36°, light output direct, with converter, max. 260mA, dimmability: not dimmable, cable black, adapter/ceiling base silver, pendant length 3000mm, IP20






### Sketch




### Technical details

| | |
|---|---|
| Light source | LED |
| System performance [W] | 12 |
| Luminous flux [lm] | 680 |
| Current sec. [mA] | 260 |
| Colour temperature | 2700K |
| CRI | >90 |
| Optics | high quality plastic lens |
| Converter | with converter |
| Dimmability | not dimmable |
| Light emission area | direct |
| Beam angle | 36° |
| Voltage | 220-240V 50/60Hz |
| | |
| Length [mm] | 3000 |
| Height [mm] | 300 |
| Length pendant [mm] | 3000 |
| Diameter [mm] | 57 |
| IP protection class | IP20 |
| IP protection class | protection cl. II |
| | |
| Material | aluminium |
| Colour of body | black |
| RAL | 9005 |
| Colour of adapter / ceiling base | silver |
| Cable | black |
| Lifetime [h] | L80 B10 20 000 |
| Energy efficiency class | G |
| | |
| Net weight [kg] | 1.19 |
| EAN number | 9010506772760 |

### Light distribution curve




Energy label

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.