



DIVO

192-2090200029560

DIVO SHORT VOLARE SUSPENSION WITH 2-PH VOLARE ADAPTER made of aluminium, white, similar to RAL 9003, high quality plastic lens beam 36°, light output direct, with converter, max. 260mA, dimmability: not dimmable, cable white, adapter/ceiling base black, pendant length 3000mm, IP20




SKETCH



TECHNICAL DETAILS

| | |
|----------------------------------|---------------------------|
| Light source | LED |
| System performance [W] | 12 |
| Luminous flux [lm] | 680 |
| Current sec. [mA] | 260 |
| Colour temperature | 3000K |
| CRI | >90 |
| Optics | high quality plastic lens |
| Converter | with converter |
| Dimmability | not dimmable |
| Light emission area | direct |
| Beam angle | 36° |
| Voltage | 220-240V 50/60Hz |
| Length [mm] | 3000 |
| Height [mm] | 300 |
| Length pendant [mm] | 3000 |
| Diameter [mm] | 57 |
| IP protection class | IP20 |
| IP protection class | protection cl. II |
| Material | aluminium |
| Colour of body | white |
| RAL | 9003 |
| Colour of adapter / ceiling base | black |
| Cable | white |
| Lifetime [h] | L80 B10 20 000 |
| Energy efficiency class | G |
| Net weight [kg] | 1.16 |
| EAN number | 9010506772968 |

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.