

VARIDO 2

149-001020213050

VARIDO 2 DARK TRACK TRACK SPOTLIGHT WITH 3 PH ADAPTER made of steel sheet, white, similar to RAL 9016, Lens optics with vacuum deposited Dark reflector beam 66°, light output direct, UGR <19, swiveling 350°, with converter, max. 850mA, dimmability: not dimmable, adapter/ceiling base white, IP20



SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	32
Luminous flux [lm]	3700
Current sec. [mA]	850
Colour temperature	2700K
CRI	>80
UGR	<19
Optics	Lens optics with vacuum deposited Dark reflector with converter
Converter	not dimmable
Dimmability	direct
Light emission area	66°
Beam angle	220-240V 50/60Hz
Voltage	
Length [mm]	844
Width [mm]	54
Height [mm]	24
IP protection class	IP20
IP protection class	protection cl. II
Material	steel sheet
Colour of body	white
RAL	9016
Colour of adapter / ceiling base	white
Lifetime [h]	L80 B10 50 000
Energy efficiency class	C
Number of luminaires B16A	47
Net weight [kg]	1.49
EAN number	9010506111897

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.