



YIRA

188-2020000129550

YIRA PD SUSPENSION made of aluminium, white, similar to RAL 9003, beam 45°, light output direct, with converter, max. 600mA, dimmability: not dimmable, cable white, adapter/ceiling base white, pendant length 3000mm, IP20




SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	6
Luminous flux [lm]	380
Current sec. [mA]	600
Colour temperature	3000K
CRI	>90
Converter	with converter
Dimmability	not dimmable
Light emission area	direct
Beam angle	45°
Voltage	220-240V 50/60Hz
Length [mm]	33
Length pendant [mm]	3000
Diameter [mm]	33
IP protection class	IP20
IP protection class	protection cl. I
Material	aluminium
Colour of body	white
RAL	9003
Colour of adapter / ceiling base	white
Cable	white
Lifetime [h]	L80 B10 20 000
Energy efficiency class	E
Net weight [kg]	0.63
EAN number	9010506763812

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.