## LOG 50

## 715-071933001400f

LOG 50 AKKU EINSATZ LIGHT INSERT made of metal, white, similar to RAL 9016, light output direct, with converter, max. 700mA, dimmability: DALI, through wiring 3x1,5mm² + 2x0,75mm², IP20 battery pack for 3 hours autonomous operation, incl. test button and status LED



### Sketch



### Technical details

| | |
|---|---|
| Light source | LED |
| System performance [W] | 33 |
| Luminous flux [lm] | 5220 |
| Current sec. [mA] | 700 |
| Colour temperature | 4000K |
| CRI | >80 |
| Converter | with converter |
| Dimmability | DALI |
| Light emission area | direct |
| Voltage | 220-240V 50/60Hz |
| Through wiring | 3x1,5mm² + 2x0,75mm² |
| Length [mm] | 1403 |
| IP protection class | IP20 |
| IP protection class | protection cl. I |
| Material | metal |
| Colour of body | white |
| RAL | 9016 |
| Lifetime [h] | L80 B10 50 000 |
| Energy efficiency class | C |
| Number of luminaires B16A | 50 |
| Net weight [kg] | 1.53 |
| EAN number | 9010506477337 |

Energy label

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.