


LENS

646-102120524060

LENS DOUBLE F FLOOR LAMP made of die-cast aluminium, black, similar to RAL 9005, lens optic with anti-glare grid beam for double workplace, light output direct / indirect, UGR <16, with converter, max. 525mA, dimmability: not dimmable, cable black, IP20 Membrane switch with USB connection (max.1A)




SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	100
Luminous flux [lm]	12020
Current sec. [mA]	525
Colour temperature	4000K
CRI	>80
UGR	<16
Optics	lens optics with glare control louvre
Converter	with converter
Dimmability	not dimmable
Light emission area	direct / indirect
Beam angle [°]	for double workplace
Voltage	220-240V AC/DC
Length [mm]	1635
Width [mm]	35
Height [mm]	2065
IP protection class	IP20
IP protection class	protection cl. I
IK value	IK05
Material	die-cast aluminium
Colour of body	black
RAL	9005
Cable	black
Lifetime [h]	L80 B10 50 000
Energy efficiency class	E
Number of luminaires B16A	22
Net weight [kg]	12.24
EAN number	9010506803211

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.