


SAVO

726-0111001349060


SAVO 11 R RECESSED SPOTLIGHT made of aluminium, black, similar to RAL 9005, high-efficiently vacuum deposited aluminium reflector beam 24°, light output direct, swiveling 355°, tilting 70°, without converter, max. 350/500/700/800mA, dimmability: see converter, IP20



SKETCH



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

Light source	LED 12W/17W/24W/28W
Luminous flux [lm]	1590/2200/2940/3290
Current sec. [mA]	350/500/700/800
Colour temperature	3000K
CRI	PREMIUM >90
Optics	vacuum deposited aluminium reflector
Converter	without converter
Dimmability	see converter
Light emission area	direct
Beam angle [°]	24°
Length [mm]	153,5
Height [mm]	105
Diameter [mm]	138
Ceiling cutout [mm]	120
Ceiling thickness [mm]	1-20
Mounting depth [mm]	135
IP protection class	IP20
IP protection class	protection cl. II
Material	aluminium
Colour of body	black
RAL	9005
Lifetime [h]	L80 B10 50 000
Energy efficiency class	E
Net weight [kg]	0.90
EAN number	9010979161245



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.