



LOG 50 RING

722-03018021140500d

LOG 50 RING 180° PDI SUSPENSION made of aluminium, white, similar to RAL 9016, satined PMMA opal diffuser light output direct / indirect, with converter, max. 700/550mA, dimmability: DALI, through wiring 3x1,5mm² + 2x0,75mm², pendant length 3000mm, IP20



SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	92
Luminous flux [lm]	12020
Current sec. [mA]	700/550
Colour temperature	4000K
CRI	>80
Optics	PMMA opal diffuser with converter
Converter	
Dimmability	DALI
Light emission area	direct / indirect
Voltage	220-240V 50/60Hz
Through wiring	3x1,5mm² + 2x0,75mm²

Length [mm]	1480
Width [mm]	52
Height [mm]	65
Length pendant [mm]	3000
Diameter [mm]	1480
IP protection class	IP20
IP protection class	protection cl. I
IK value	IK03


Material	aluminium
Colour of body	white
RAL	9016
Lifetime [h]	L80 B10 50 000
Energy efficiency class	C
Number of luminaires B16A	12

Net weight [kg]	8.22
EAN number	9010870237742



Energy label

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.