



LENS

646-11206052408t

LENS TRIPLE F FLOOR LAMP made of die-cast aluminium, natural anodised, similar to RAL 9006, lens optic with anti-glare grid beam for triple workplace, light output direct / indirect, UGR <16, with converter, max. 525mA, dimmability: Push Dim, cable black, IP20 rocker button




SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	100
Luminous flux [lm]	12020
Current sec. [mA]	525
Colour temperature	4000K
CRI	>80
UGR	<16
Optics	lens optics with glare control louvre
Converter	with converter
Dimmability	Push Dim
Light emission area	direct / indirect
Beam angle	for triple workplace
Voltage	220-240V AC/DC
Length [mm]	2035
Width [mm]	35
Height [mm]	2065
IP protection class	IP20
IP protection class	protection cl. I
IK value	IK05
Material	die-cast aluminium
Colour of body	aluminium anodised
RAL	9006
Cable	black
Lifetime [h]	L80 B10 50 000
Energy efficiency class	E
Number of luminaires B16A	18
Net weight [kg]	12.70
EAN number	9010506804706

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.