



CONCEPT

723-00112011466t

CONCEPT RIGHT F FLOOR LAMP made of aluminium, black, similar to RAL 9005, microfaceted free-form reflector beam for single workplace, light output direct / indirect 30:70, UGR <19, with converter, max. 1500mA, dimmability: Push Dim, cable black, IP20 Membrane switch with USB connection (max.1A)




SKETCH



TECHNICAL DETAILS

Light source	LED
System performance [W]	70
Luminous flux [lm]	7710
Current sec. [mA]	1500
Colour temperature	4000K
CRI	>80
UGR	<19
Optics	microfaceted free-form reflector
Converter	with converter
Dimmability	Push Dim
Light emission area	direct / indirect 30:70
Beam angle	for single workplace
Voltage	220-240V AC/DC
Length [mm]	355
Width [mm]	131
Height [mm]	2077
IP protection class	IP20
IP protection class	protection cl. I
Material	aluminium
Colour of body	black
RAL	9005
Cable	black
Lifetime [h]	L80 B10 50 000
Energy efficiency class	D
Number of luminaires B16A	24
Net weight [kg]	12.80
EAN number	9010506308358

LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.  
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.