



LOG 50

715-1704130414000

LOG 50 OFFICE EINSATZ LIGHT INSERT made of metal, Lens optics with vacuum deposited synthetic reflector beam 66°, light output direct, UGR <16, with converter, max. 550mA, dimmability: not dimmable, through wiring 3x1,5mm², IP20



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

Light source	LED
System performance [W]	25
Luminous flux [lm]	3840
Current sec. [mA]	550
Colour temperature	4000K
CRI	>80
UGR	<16
Optics	Lens optics with vacuum deposited synthetic reflector with converter
Converter	with converter
Dimmability	not dimmable
Light emission area	direct
Beam angle	66°
Voltage	220-240V 50/60Hz
Through wiring	3x1,5mm²
Length [mm]	1402,5
Width [mm]	49
Height [mm]	50
IP protection class	IP20
IP protection class	protection cl. I
Material	metal
Lifetime [h]	L80 B10 50 000
Energy efficiency class	D
Number of luminaires B16A	50
Net weight [kg]	1.78
EAN number	9010870548855



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.