

LOG 50 RING

722-0201b021190500d

LOG 50 RING 90° PD SUSPENSION made of aluminium, white, similar to RAL 9016, satined PMMA opal diffuser light output direct, with converter, max. 700mA, dimmability: DALI, through wiring 3x1,5mm² + 2x0,75mm², pendant length 3000mm, IP20

SKETCH



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

| | |
|---------------------------|--|
| Light source | LED |
| System performance [W] | 19 |
| Luminous flux [lm] | 2590 |
| Current sec. [mA] | 700 |
| Colour temperature | 3000K |
| CRI | >80 |
| Optics | PMMA opal diffuser |
| Converter | with converter |
| Dimmability | DALI |
| Light emission area | direct |
| Voltage | 220-240V 50/60Hz |
| Through wiring | 3x1,5mm ² + 2x0,75mm ² |
| Length [mm] | 562,5 |
| Width [mm] | 52 |
| Height [mm] | 65 |
| Length pendant [mm] | 3000 |
| Diameter [mm] | 1125 |
| IP protection class | IP20 |
| IP protection class | protection cl. I |
| IK value | IK03 |
| Material | aluminium |
| Colour of body | white |
| RAL | 9016 |
| Lifetime [h] | L80 B10 50 000 |
| Energy efficiency class | C |
| Number of luminaires B16A | 50 |
| Net weight [kg] | 3,34 |
| EAN number | 9010870199811 |



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
 Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.