




LOG 50

716-0201141019600


LOG 50 PD SUSPENSION made of aluminium, black, similar to RAL 9005, sated PMMA opal diffuser light output direct, with converter, max. 350mA, dimmability: not dimmable, cable transparent, adapter/ceiling base black, pendant length 1500mm, IP20



SKETCH



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

Light source	LED
System performance [W]	20
Luminous flux [lm]	2570
Current sec. [mA]	350
Colour temperature	3000K
CRI	>80
Optics	PMMA opal diffuser
Converter	with converter
Dimmability	not dimmable
Light emission area	direct
Voltage	220-240V 50/60Hz
Length [mm]	1687
Width [mm]	52
Height [mm]	66
Length pendant [mm]	1500
IP protection class	IP20
IP protection class	protection cl. I
IK value	IK04
Material	aluminium
Colour of body	black
RAL	9005
Colour of adapter / ceiling base	black
Cable	transparent
Lifetime [h]	L80 B10 50 000
Energy efficiency class	C
Number of luminaires B16A	25
Net weight [kg]	4.70
EAN number	9010506585865



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.  
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.