

PHILIPS

30-880206


XITANIUM MINI, white, non-dimmable, secondary wire cross-section up to 1.5mm², primary wire cross-section up to 2.5mm², protection against overheating and short-circuiting, mains overvoltages, overload, ceiling cut-out = 53mm, adjustable via DIP-SWITCH (see B3): Constant current
L156mm, W=43mm, H=30mm
220-240V 50/60Hz



TECHNICAL DETAILS

System performance [W]	40
Dimmability	not dimmable
Voltage	220-240V 50/60Hz
Length [mm]	156
Width [mm]	43
Height [mm]	30
Ceiling cutout [mm]	53
IP protection class	IP20
IP protection class	protection cl. II
Material	synthetic
Colour of body	white
Number of luminaires B16A	48
Net weight [kg]	0.14
EAN number	9010870551855

SKETCH



LIGHT DISTRIBUTION CURVE

mA	W	V DC
700	30	5-44
750	33	5-44
800	35	5-44
850	37	5-44
900	39	5-44
950	40	5-44
1000	40	5-40
1050	40	5-38



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.