

## SATOR

305-30013500

SATOR ROUND R RECESSED SPOTLIGHT made of aluminium, white, similar to RAL 9003, beam 24°, light output direct, tilting 30°, with converter, max. 250mA, dimmability: see converter, IP44/IP20




## SKETCH



1 - 20 mm

Ø 68 mm, **ET 119 mm**




## TECHNICAL DETAILS

|                         |                    |
|-------------------------|--------------------|
| Light source            | LED 9W             |
| Luminous flux [lm]      | 600                |
| Current sec. [mA]       | 250                |
| Colour temperature      | 2700K              |
| CRI                     | >90                |
| Converter               | with converter     |
| Dimmability             | see converter      |
| Light emission area     | direct             |
| Beam angle              | 24°                |
| Voltage                 | 36 VDC             |
| Height [mm]             | 89                 |
| Diameter [mm]           | 72                 |
| Ceiling cutout [mm]     | 68                 |
| Mounting depth [mm]     | 119                |
| IP protection class     | IP44/IP20          |
| IP protection class     | protection cl. III |
| Material                | aluminium          |
| Colour of body          | white              |
| RAL                     | 9003               |
| Lifetime [h]            | L80 B10 20 000     |
| Energy efficiency class | G                  |

|                 |               |
|-----------------|---------------|
| Net weight [kg] | 0.24          |
| EAN number      | 9010506136777 |

## LIGHT DISTRIBUTION CURVE



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.  
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.