

## TCI

24-122203

multipower driver, not dimm.; 100mA 5,4W / 140mA 7,7W / 180mA 9,9W / 220mA 12W /  
 260mA 14,3W / 300mA 16,5W / 340mA 18,6W / 380mA 20W  
 24V DC 9W (380mA max.)  
 ceiling cut out =55mm



## TECHNICAL DETAILS

System performance [W]	5,4-20
Dimmability	not dimmable
Voltage	220-240V 50/60Hz
Length [mm]	111
Width [mm]	52
Height [mm]	22
IP protection class	IP20
IP protection class	protection cl. II
Material	synthetic
Colour of body	white
Number of luminaires B16A	50
Net weight [kg]	0.08
EAN number	8010703310971

## LIGHT DISTRIBUTION CURVE

DIP-SWITCH Einstellungen: 24-122203		
P out W	V out DC	I out DC
5,4W	20 ... 54	100mA Konstantstrom
7,5W	10 ... 54	140mA Konstantstrom
10W	2 ... 54	180mA Konstantstrom
12W	2 ... 54	220mA Konstantstrom
14W	2 ... 54	260mA Konstantstrom
16W	2 ... 54	300mA Konstantstrom
18W	2 ... 54	340mA Konstantstrom
20W	2 ... 54	380mA Konstantstrom
9W	24	Max. 380mA Konstantspannung



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.  
 Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.