

## SAVO

633-00302084906v3

SAVO 20 SQUARE DOUBLE R RECESSED SPOTLIGHT made of aluminium, black, similar to RAL 9005, high-efficiently vacuum deposited aluminium reflector beam 40°, light output direct, swiveling 355°, tilting 30°, without converter, max. 350/500/700mA, dimmability: see converter, IP20



## TECHNICAL DETAILS

|                         |                                      |
|-------------------------|--------------------------------------|
| Light source            | LED 12/17/24W                        |
| Number of sockets       | 2x                                   |
| Luminous flux [lm]      | 3080/4240/5710                       |
| Current sec. [mA]       | 350/500/700                          |
| Colour temperature      | 3000K                                |
| CRI                     | PREMIUM>90                           |
| Optics                  | vacuum deposited aluminium reflector |
| Converter               | without converter                    |
| Dimmability             | see converter                        |
| Light emission area     | direct                               |
| Beam angle              | 40°                                  |
| Length [mm]             | 325                                  |
| Width [mm]              | 175                                  |
| Height [mm]             | 140                                  |
| Ceiling cutout [mm]     | 305x155                              |
| Ceiling thickness [mm]  | 1-25                                 |
| Mounting depth [mm]     | 179                                  |
| IP protection class     | IP20                                 |
| IP protection class     | protection cl. II                    |
| Material                | aluminium                            |
| Colour of body          | black                                |
| RAL                     | 9005                                 |
| Lifetime [h]            | L80 B10 50 000                       |
| Energy efficiency class | C                                    |
| Net weight [kg]         | 2.34                                 |
| EAN number              | 9010979840423                        |



Energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%.  
Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.